


**R A E**
**Runau Electronics(Yangzhou)Manufacturing Co.,Ltd**
**YC451 - Power Thyristor**
**500 - 2000 V<sub>DRM</sub>; 2400 A rms**

\*\*\*\*\*  
**HIGH POWER THYRISTOR FOR PHASE CONTROL APPLICATIONS**
**Features:**

- . All Diffused Structure
- . Interdigitated Amplifying Gate Configuration
- . Blocking capability up to 2000 volts
- . Guaranteed Maximum Turn-Off Time
- . High dV/dt Capability
- . Pressure Assembled Device

**ELECTRICAL CHARACTERISTICS AND RATINGS**
**Blocking - Off State**


Device Type	V <sub>RRM</sub> (1)	V <sub>DRM</sub> (1)	V <sub>RSM</sub> (1)
YC451E	500	500	600
YC451P	1000	1000	1100
YC451PD	1400	1400	1500
YC451PM	1600	1600	1700
YC451PN	1800	1800	1900
YC451L	2000	2000	2100

V<sub>RRM</sub> = Repetitive peak reverse voltage

V<sub>DRM</sub> = Repetitive peak off state voltage

V<sub>RSM</sub> = Non repetitive peak reverse voltage (2)

Repetitive peak reverse leakage and off state leakage	I <sub>RRM</sub> / I <sub>DRM</sub>	15 mA 65 mA (3)
Critical rate of voltage rise	dV/dt (4)	400 V/μsec



## Notes:

All ratings are specified for T<sub>j</sub>=25 °C unless otherwise stated.

(1) All voltage ratings are specified for an applied 50Hz/60Hz sinusoidal waveform over the temperature range -40 to +125 °C.

(2) 10 msec. max. pulse width

(3) Maximum value for T<sub>j</sub> = 125 °C.

(4) Minimum value for linear and exponential waveshape to 80% rated V<sub>DRM</sub>. Gate open. T<sub>j</sub> = 125 °C.

(5) Non-repetitive value.

(6) The value of di/dt is established in accordance with EIA/NIMA Standard RS-397, Section 5-2-2-6. The value defined would be in addition to that obtained from a snubber circuit, comprising a 0.2 μF capacitor and 20 ohms resistance in parallel with the thristor under test.

**Conducting - on state**

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Average value of on-state current	I <sub>T(AV)</sub>		1500		A	Sinewave, 180° conduction, T <sub>c</sub> =65°C
RMS value of on-state current	I <sub>TRMS</sub>		2400		A	Nominal value
Peak one cycle surge (non repetitive) current	I <sub>TSM</sub>		23000 21000		A A	8.3 msec (60Hz), sinusoidal wave- shape, 180° conduction, T <sub>j</sub> = 125 °C 10.0 msec (50Hz), sinusoidal wave- shape, 180° conduction, T <sub>j</sub> = 125 °C
I square t	I <sup>2</sup> t		2.2x10 <sup>6</sup>		A <sup>2</sup> s	8.3 msec
Latching current	I <sub>L</sub>		800		mA	V <sub>D</sub> = 24 V; R <sub>L</sub> = 12 ohms
Holding current	I <sub>H</sub>		400		mA	V <sub>D</sub> = 24 V; I = 2.5 A
Peak on-state voltage	V <sub>TM</sub>		1.65		V	I <sub>TM</sub> = 3000 A;
Critical rate of rise of on-state current (5, 6)	di/dt		400		A/μs	Switching from V <sub>DRM</sub> ≤ 1000 V, non-repetitive
Critical rate of rise of on-state current (6)	di/dt		150		A/μs	Switching from V <sub>DRM</sub> ≤ 1000 V

**ELECTRICAL CHARACTERISTICS AND RATINGS (cont'd)**

YC451 - Power Thyristor

**Gating**

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Peak gate power dissipation	P <sub>GM</sub>		200		W	t <sub>p</sub> = 40 us
Average gate power dissipation	P <sub>G(AV)</sub>		5		W	
Peak gate current	I <sub>GM</sub>		10		A	
Gate current required to trigger all units	I <sub>GT</sub>		300 200 125		mA	V <sub>D</sub> = 6 V; R <sub>L</sub> = 3 ohms; T <sub>j</sub> = -40 °C
					mA	V <sub>D</sub> = 6 V; R <sub>L</sub> = 3 ohms; T <sub>j</sub> = +25 °C
					mA	V <sub>D</sub> = 6 V; R <sub>L</sub> = 3 ohms; T <sub>j</sub> = +125 °C
Gate voltage required to trigger all units	V <sub>GT</sub>	0.30	5 3		V	V <sub>D</sub> = 6 V; R <sub>L</sub> = 3 ohms; T <sub>j</sub> = -40 °C
					V	V <sub>D</sub> = 6 V; R <sub>L</sub> = 3 ohms; T <sub>j</sub> = 0-125 °C
					V	V <sub>D</sub> = Rated V <sub>DRM</sub> ; R <sub>L</sub> = 1000 ohms; T <sub>j</sub> = + 125 °C
Peak negative voltage	V <sub>GRM</sub>		5		V	

**Dynamic**

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Delay time	t <sub>d</sub>		1.5	0.7	μs	I <sub>TM</sub> = 50 A; V <sub>D</sub> = 67% V <sub>DRM</sub> Gate pulse: V <sub>G</sub> = 30 V; R <sub>G</sub> = 10 ohms; t <sub>r</sub> = 0.1 μs; t <sub>p</sub> = 20 μs
Turn-off time (with V <sub>R</sub> = -5 V)	t <sub>q</sub>		250	150	μs	I <sub>TM</sub> > 1000 A; di/dt = 25 A/μs; V <sub>R</sub> ≥ -5 V; Re-applied dV/dt = 20V/μs linear to 67% V <sub>DRM</sub> ; T <sub>j</sub> = 125 °C; Duty cycle ≥ 0.01%
Reverse recovery charge	I <sub>rr</sub>		*		μC	I <sub>TM</sub> > 1000 A; di/dt = 25 A/μs; V <sub>R</sub> ≥ -50 V; T <sub>j</sub> = 125 °C

**THERMAL AND MECHANICAL CHARACTERISTICS AND RATINGS**

Parameter	Symbol	Min.	Max.	Typ.	Units	Conditions
Operating temperature	T <sub>j</sub>	-40	+125		°C	
Storage temperature	T <sub>stg</sub>	-40	+150		°C	
Thermal resistance - junction to case	R <sub>Θ(j-c)</sub>		0.025 0.050		°C/W	Double sided cooled Single sided cooled
Thermal resistamce - case to sink	R <sub>Θ(c-s)</sub>		0.010 0.020		°C/W	Double sided cooled * Single sided cooled
Mounting force	P	5000 24.5	6000 26.4		lb. kN	
Weight	W			16 0.46	oz Kg.	

\* Mounting surfaces smooth, flat and greased

